

Working With Aluminum?

The Gerson 9900 Full Face Mask with our G71 combination OV/P100 cartridges can protect against hazardous exposure due to welding and the dust caused from working with aluminum.



The Hazards Of Working With Aluminum

Aluminum Dust, Fumes and Ozone are known to cause irritation to eyes, skin, nose, throat and/or damage to the central nervous system.

See NIOSH pocket guide to chemicals for further information.*

GERSON®
Leading the Way

WWW.GERSONCO.COM • 508.947.4000
16 Commerce Blvd., Middleboro, MA 02346

WARNINGS: Before use, the user must first determine that the respirator properly fits. A fit test must be performed in accordance with 29CFR 1910.134. All users of safety products must undergo thorough training and all warnings and instructions provided with the products must be read and understood prior to use.

*Not NIOSH approved for Ozone protection. "Nuisance Level" refers to concentrations not exceeding the OSHA PEL or applicable government standards for exposure limits, whichever is lower.



GERSON®

Full-Face TPE Respirator With Organic Vapor, P100 Respirator Cartridges

Working With Aluminum?

The Gerson One-Size Fits All Full-Face Respirator with our G71 combination OV/P100 Cartridges is the recommended solution:

- NIOSH-Approved protection for **metal fumes** that are generated during Aluminum Welding.
- NIOSH-Approved particulate filter provides at least **99.97%** filtration efficiency against **particulates** generated in sanding and grinding applications in the Body Shop*.
- Relief from the irritating effects of nuisance level **Ozone****.
- NIOSH-Approved protection for **Paint-Spray** and other Organic Vapors.*
- Includes 1 Full-Face Facepiece, 4 OV/P100 Cartridges, 5 Protective Lens Peel-Offs and **FREE** Lanyard.



PACKAGING

ITEM NUMBER	MASK MATERIAL	MASTER PACKAGING	CASE WEIGHT	CASE DIMENSIONS	CASE CUBE	CASE BARCODE
089901-KIT4	TPE	1/box, 1/case	3 lbs	10" x 9" x 6"	0.3125 cf	0-44585-89901-7

***WARNINGS:** Before use, the user must first determine that the respirator properly fits. A fit test must be performed in accordance with 29CFR 1910.134. All users of safety products must undergo thorough training and all warnings and instructions provided with the products must be read and understood prior to use. It is necessary to assess the work environment and concentrations of hazardous substances that may exist in the workplace in order to determine the appropriate protective equipment. This product does not supply Oxygen. User must maintain at least 19.5% Oxygen in the workplace. Do not use in or around sandblasting.

****Not NIOSH approved for Ozone protection.** "Nuisance Level" refers to concentrations not exceeding the OSHA PEL or applicable government standards for exposure limits, whichever is lower.

Distributed by: